
CABLES UNIFILAR INDOOR CAT.6

100010214779 - 4778



1	JCKET
2	RIP CORD
3	PE CROSS
4	TWISTED PAIR

DESCRIPTION	
Rated Voltage (V)	N/A
Rated Temperature (°C)	75
Product Standard Certification	N/A
APPLICATION	
Telephone and other communication circuits such as voice, data, and audio for on-premise customer systems.	
10/100/1000Base-T	
155Mbps ATM	
REFERENCE STANDARD	
TIA-568-C.2	
FLUCK DTX-1800 PERMANENT LINK TEST	

CONSTRUCTION	
Conductor	Solid Bare Copper
4 Twisted Pair	8C
AWG	23
Construction (±0.02mm)	1/0.57
Insulation	PE
Nom. Thickness (mm)	0.20
Insulation Dia.(±0.08mm)	1.03
Cabled together Separator	PE CROSS
Jacket	PVC
Nom. Thickness (mm)	0.50
Outer Dia. (±0.30mm)	6.30

UNIFILAR INDOOR	
100010214778	UTP LSZH CAT. 6 Azul
100010214779	UTP PVC CAT. 6 Gris

CABLES UNIFILAR INDOOR CAT.6

100010214779 - 4778

PERFORMANCE						
Electrical Characteristics (20ºC)						
Max. Conductor DC Resistance (Ω/km)			93			
Min. Insulation Resistance (ΩM-KM)			100M			
Mutual Capacitance			≤ 5.6nF/100M			
Dielectric Strengt			DC-1KV/1 Min			
Environmental Requirement			RoHS compliant			
F	**ATTN**	**RL**	**NEXT**	**ELFEXT**	**PS NEXT**	**PS ELFEXT**
(MHz)	(dB/100m)	(dB)	(dB)	(dB/100m)	(dB/100m)	(dB/100m)
1	1.9	20.0	74.3	67.8	72.3	64.8
4	3.7	23.3	65.3	61.8	63.3	52.8
8	5.3	24.5	60.3	55.7	58.8	46.7
10	5.9	25.0	59.3	53.8	57.3	44.8
16	7.5	25.0	56.3	49.7	54.3	40.7
20	8.4	25.0	54.8	47.8	52.8	38.7
25	9.5	24.3	53.4	45.8	51.4	36.8
31.25	10.6	23.6	51.9	43.9	49.9	34.9
62.5	15.4	21.5	47.4	37.9	45.4	28.8
100	19.8	20.1	44.3	33.8	42.3	24.8
155	25.1	18.8	41.4	27.8	39.4	20.9
200	29.0	18.0	39.8	25.8	37.8	18.7
250	32.8	17.3	38.3	24.3	36.3	16.8

CABLES UNIFILAR INDOOR CAT.6

100010214779 - 4778

Cat 6 Perm. Link													
Wire Map	Res	Leng-th	Prop. Delay	Delay Skew	Freq	Insertion Loss	NEXT	RL	ACR-N	ACR-F	PS NEXT	PS ACR-N	PS ACR-F
	Ω	Max.	nS	nS	MHz	dB	dB	dB	dB	dB	dB	dB	dB
12345678	i	90 m	498	44	1	3	65.0	19.1	62.0	64.2	62.0	59.0	61.2
12345678					4	3.5	64.1	21.0	60.6	52.1	61.8	58.3	49.1
					8	5	59.4	21.0	54.4	46.1	57.0	52.1	43.1
12345678S					10	5.5	57.8	21.0	52.3	44.2	55.5	49.9	41.2
12345678S					16	7	54.6	20.0	47.6	40.1	52.2	45.2	37.1
					20	7.9	53.1	19.5	45.2	38.2	50.7	42.8	35.2
					25	8.9	51.5	19.0	42.7	36.2	49.1	40.2	33.2
					31.25	10	50.0	18.5	40.0	34.3	47.5	37.6	31.3
					62.5	14.4	45.1	16.0	30.8	28.3	42.7	28.3	25.3
					100	18.6	41.8	14.0	23.3	24.2	39.3	20.7	21.2
					200	27.4	36.9	11.0	9.6	18.2	34.3	7.0	15.2
					250	31.1	35.3	10.0	4.2	16.2	32.7	1.6	13.2